

MANUFACTURER	DESCRIPTION	QTY	NOTES
WELLHEAD CASING HEADS (BRADEN HEADS) 'A' SECTION			
CIW	13 3/8" 5K X 13 5/8" SOW	1	2" LP-NPT OUTLETS
CIW	13 5/8" 3K X 13 3/8" BTC	1	2 1/16" 5M OUTLETS 1208-22-10-P
CIW	13 5/8" 3K X 13 3/8" BTC TYPE S	1	2" LP-NPT OUTLETS 2070323-01-01 'CC'
FMC-APV	11" 3K X 9 5/8" SOW C22	2	2" LP-NPT OUTLETS
FMC-APV	11" 3K X 9 5/8" LTC C22	1	2" LP-NPT OUTLETS
FMC	13 5/8" 3K X 13 3/8" BTC	1	2" LP-NPT OUTLETS
FMC	21 1/4" 2K X 20" SOW C22	3	2" LP-NPT OUTLETS

ABBREVIATIONS:- 2K=2000PSI, 3K=3000PSI, 5K=5000PSI, BTC=BUTTRESS THREAD, LP=LINE PIPE SCREWED (NPT), LTC=LONG THREAD CASING (8RD), SOW=SLIP ON WELD.

GLOBAL SUPPLY LINE PRODUCT RANGE WELLHEAD EQUIPMENT

OCT (FMC®™) AND CAMERON®™ (CIW) STYLES, BRADEN HEADS (CASING HEADS), CASING SPOOLS, TUBING SPOOLS, CHRISTMAS TREES, ADAPTOR FLANGES, ADAPTOR SPOOLS, VALVES AND CHOKES. X-BUSHINGS, FBBEN AND TCIA TUBING HANGERS, CA AND CW CASING SLIPS, NIPPLES, LUBRICATES BPV VALVES ETC.

1 13/16 INCH, 2 1/16 INCH 2 9/16 INCH, 3 1/8 INCH, 3 1/16 INCH, 4 1/16 INCH, 7 1/16 INCH, 9 INCH, 11 INCH, 13 5/8 INCH, 16 3/4 INCH, 21 1/4 INCH, 20 3/4 INCH.

API6A 200 LB (2000 PSI), 3000 LB (3000 PSI), 5000 LB (5000 PSI), 10000 LB (10000 PSI), 15000 LB (15000 PSI).

UNLESS STATED ALL ITEMS ARE TO API6A AND FORGED IN 4130 OR 4140 GRADE AS STANDARD, PSL2 (DUAL CONFORMS PSL1), 'EE' TRIM (DUAL CONFORM AA,BB,DD) PR1, PR2, TEMP 'Y' (DUAL CONFORMING TO K,L,M,N). NACE MR-01-75 MOST ITEMS. MANUFACTURED BY API6A LICENSED MANUFACTURERS. ALL ITEMS ARE FULLY INTEGRAL NO WELDS.

WE CAN SUPPLY WELLHEAD EQUIPMENT COMPATIBLE WITH CAMERON, FMC AND OTHER MAJORS IN VERY SHORT DELIVERY SOURCING FROM OUR USA AND EUROPEAN API6A LICENSE MANUFACTURERS.

www.globalsupplyline.com.au