

SAFETY VALVES (SSDV)



TYPE	SIZE INCH	RATING	PSI	ENDS	MAKER	DESCRIPTION	BODY	TRIM	NOTES	QTY	
SAFETY	2	1/16	5000	PSI	RTJ	APV-NEWAY	SLAB, FP, TC, FC, H2S, PNEU HWOP, NACE	A4874C 413060K	"EE",T=410 HF, S=410 HF+PTFE,G=410 HF, ST=174PH-HF, PSL 3, PR1, L7M	SR PNEUMATIC FAIL CLOSED SPRING RETURN REVERSE ACTING GATE MANUAL OVER-RIDE, 316, L-X, 6A, 60K S24 TRIM	2

ABBREVIATIONS:-

DIAPH= DIAPHRAGM ACTUATOR, **"EE"**=EE TRIM, **EXP**=EXPANDING GATE, **FP**=FULL PORT, **FCSR**=FAIL CLOSED SPRING RETURN, **G**=GATE, **HF**=STELLITE #6, **HWOP**=HAND WHEEL OVER-RIDE, **L7M**=A320 GR L7M BOLTS, **NACE**=NACE MR0175, **PNEU**=PNEUMATIC, **S**=SEAT, **SLAB**=SLAB GATE FLOATING SEATS, **T**=TRIM

www.globalsupplyline.com.au