


TYPE	SIZE INCH	RATING	ENDS	MANUFACTURER	DESCRIPTION	BODY	TRIM	QTY
GATE-API	2 1/16	5000	PSI NPT	APV-NEWAY	MUD FP DM H2S HW	A4874C	DD 410+VITON SEAT PSL2 PR1 T24	16
GATE-API	2 1/16	5000	PSI RTJ	APV-NEWAY	EXP TC M H2S HW	A4874C	EE 410HF+HF SEAT PSL2 PR1 S24	20
GATE-API	2 1/16	5000	PSI RTJ	APV-NEWAY	SLAB TC FC H2S SSDV PNEUMATIC SR A	A4874C	EE 410HF+HF SEAT PSL2 PR1 S24	2
GATE-API	2 1/16	5000	PSI RTJ	APV-NEWAY	EXP TC M GEN HW	A4874C	BB 410HF+PTFE SEAT PSL2 PR1 T22	18
GATE-API	2 1/16	5000	PSI NPT 2"	APV-NEWAY	EXP TC M H2S HW	A4874C	DD 410HF SEAT PSL2 PR1	20
GATE-API	2 1/16	5000	PSI BW160	APV-NEWAY	MUD FP DM H2S HW	A4874C	DD 410+VITON SEAT PSL2 PR1 T24	20
GATE-API	2 1/16	5000	PSI BWXXS	APV-NEWAY	MUD FP DM H2S HW	A4874C	DD 410+VITON SEAT PSL2 PR1 T24	20
GATE-API	2 1/16	5000	PSI RTJ	APV-NEWAY	MUD FP DM H2S HW	A4874C	DD 410+VITON SEAT PSL2 PR1 T24	18
GATE-API	2 1/16	10000	PSI RTJ	APV-NEWAY	SLAB TC M GEN HW	4130	BB 410HF+PTFE SEAT PSL2 PR1 T22	6
GATE-API	2 9/16	5000	PSI BWXXS	APV-NEWAY	MUD FP DM H2S HW	A4874C	DD 410+VITON SEAT PSL2 PR1 T24	5
GATE-API	2 9/16	5000	PSI RTJ	APV-NEWAY	EXP TC M H2S HW	A4874C	DD 410HF+HF SEAT PSL2 PR1 S24	10
GATE-API	2 9/16	5000	PSI RTJ	APV-NEWAY	EXP TC M H2S HW	A4874C	DD 410HF+PTFE SEAT PSL2 PR1 T24	4
GATE-API	3 1/8	3000	PSI RTJ	APV-NEWAY	MUD FP DM H2S HW	A4874C	DD 316+VITON SEAT PSL2 PR1 T24	4
GATE-API	3 1/8	3000	PSI RTJ	APV-NEWAY	EXP TC M H2S HW	A4874C	EE 410 410HF+HF SEAT PSL2 PR1 S24	6
GATE-API	3 1/8	3000	PSI RTJ	APV-NEWAY	MUD FP DM H2S HW	A4874C	DD 410HF+HNBR SEAT PSL2 PR1 T24	3
GATE-API	3 1/8	3000	PSI RTJ	APV-NEWAY	EXP TC M H2S HW	A4874C	EE 410 410HF+PTFE SEAT PSL2 PR1 S24	8
GATE-API	3 1/8	5000	PSI RTJ	APV-NEWAY	MUD FP DM H2S HW	A4874C	DD 410F+HNBR SEAT PSL2 PR1 T24	1
GATE-API	3 1/8	5000	PSI BWXXS	APV-NEWAY	MUD FP DM H2S HW	A4874C	DD 410F+HNBR SEAT PSL2 PR1 T24	10
GATE-API	3 1/8	5000	PSI BW160	APV-NEWAY	MUD FP DM H2S HW	A4874C	DD 410HF+HF SEAT PSL2 PR1 T24	4
GATE-API	3 1/8	5000	PSI RTJ	APV-NEWAY	MUD FP DM H2S HW	A4874C	DD 410F+HNBR SEAT PSL2 PR1 T24	1
GATE-API	3 1/8	5000	PSI NPT 3"	APV-NEWAY	EXP TC M H2S HW	A4874C	BB 410HF+PTFE SEAT PSL2 PR1 T22	2
GATE-API	3 1/8	5000	PSI RTJ	APV-NEWAY	EXP TC M H2S HW	A4874C	DD 410HF+HF SEAT PSL2 PR1 S24	3
GATE-API	3 1/8	5000	PSI RTJ	APV-NEWAY	EXP TC M H2S HW	A4874C	EE 410 410HF+PTFE SEAT PSL2 PR1 S24	4
GATE-API	3 1/8	5000	PSI NPT	APV-NEWAY	EXP TC M H2S HW	A4874C	DD 410HF+PTFE SEAT PSL2 PR1 T22	2
GATE-API	3 1/8	5000	PSI RTJ	APV-NEWAY	EXP TC M H2S HW	A4874C	EE 410 410HF+HF SEAT PSL2 PR1 S24	4
GATE-API	3 1/8	5000	PSI RTJ	APV-NEWAY	EXP TC M H2S HW	A4874C	EE 410 410HF+PTFE/HF SEAT PSL2 PR1 S24	3
GATE-API	3 1/16	10000	PSI RTJ	APV-NEWAY	SLAB TC FL697333-19-2 HW	4140	DD 410HF+HF SEAT PSL2 PR1 S24	1
GATE-API	4 1/16	1000	PSI EUE	APV-NEWAY	MUD FP OTECO H2S HW FRAC	A4874C	DD 410HF+VITON SEAT PSL2 PR1 T24	10*
GATE-API	4 1/16	3000	PSI RTJ	APV-NEWAY	MUD FP DM H2S HW	A4874C	DD 410HF+VITON SEAT PSL2 PR1 T24	1
GATE-API	4 1/16	3000	PSI BW160	APV-NEWAY	MUD FP DM H2S HW	A4874C	DD 410HF+VITON SEAT PSL2 PR1 T24	1
GATE-API	4 1/16	3000	PSI NPT	APV-NEWAY	MUD FP DM H2S HW	A4874C	DD 410HF+VITON SEAT PSL2 PR1 T24	2
GATE-API	4 1/16	3000	PSI RTJ	APV-NEWAY	EXP TC M H2S HW	A4874C	EE 410HF+PTFE/HF SEAT PSL2 PR1 S24	4
GATE-API	4 1/16	750	PSI EUE	APV-NEWAY	MUD FP OTECO H2S HW FRAC	A4874C	DD 410HF+VITON SEAT PSL2 PR1 T24	4*
GATE-API	4 1/16	3000	PSI RTJ	APV-NEWAY	SLAB TC FL H2S 140504-21-51-09 HW	A4874C	EE 316+HF SEAT PSL2 PR1 S24	2
GATE-API	4 1/16	3000	PSI RTJ	APV-NEWAY	SLAB TC M20 H2S HW	410	CC 410 410HF PSL2 PR1 FB	2
GATE-API	4 1/16	5000	PSI RTJ	APV-NEWAY	EXP TC M H2S HW	A4874C	EE 410HF+HF SEAT PSL2 PR1 S24	4
GATE-API	4 1/16	5000	PSI BWXXS	APV-NEWAY	MUD FP DM H2S HW	A4874C	DD 410HF+VITON SEAT PSL2 PR1 T24	8
GATE-API	4 1/16	5000	PSI RTJ	APV-NEWAY	MUD FP DM H2S HW	A4874C	DD 410HF+VITON SEAT PSL2 PR1 T24	11
GATE-API	7 1/16	5000	PSI RTJ	APV-NEWAY	EXP TC M H2S HW 7 1/16" PORT	4130	EE 410HF+HF SEAT 17-4PH ST PSL2 PR1 S24	2
<b>SAFETY</b>	2 1/16	5000	PSI RTJ	APV-NEWAY	SLAB TC FC H2S PNEU SR <b>ESDV</b> HW	4130	EE 410 410HF+PTFE/HF PSL2 PR1 S24	1

\*5 DAYS DELIVERY TIME



Ball Valve c/w Integral Hammer Union ends for Quick Changeouts on Tanker Unloading Manifolds



4 1/16" EUE 3/5000 PSI Light weight Mud Gate Valve for fracking and production manifolds, very light, lasts 5-10 times longer

**ABBREVIATIONS:-**

**DM**=MODEL DM STYLE, **ESDV**=EMERGENCY SHUTDOWN VALVE, **EUE**=8RD, **EXP**=EXPANDING WKM<sup>®</sup> TM STYLE MOD 'M' GATE, **F TO F**=FACE TO FACE, **FC**=CAMERON<sup>®</sup> TM FC STYLE, **FP**=FULL PORT, **FRAC**=FRACKING VALVE LIGHT WEIGHT DESIGN LONG LIFE, **GEN**=GENERAL SERVICE, **GO**=GEAR OPERATION, **GRP**=GRAPHITE, **GSKT**=GASKET, **HF**=STELLITE #6, **HW**=HANDWHEEL, **H2S**=SOUR SERVICE NACE MR-01-75, **M**=MODEL M (WKM<sup>®</sup> STYLE), **MUD**='DM' STYLE MUD GATE, **NPT**=NATIONAL PIPE THREAD FEMALE (LP), **PNEU**=PNEUMATIC, **RTJ**=RING JOINT GASKET, **SLAB**=SLAB GATE, **SR**=SPRING RETURN, **ST**=STEM, **TC**=FULL THROUGH CONDUIT, **TCI**=TUNGSTEN CONDUIT

THIS LIST INCLUDES EX STOCK OILFIELD GATE VALVES TO API6A GATE-API EXPANDING AND SLAB PARALLEL GATE, FLOATING SLAB TO SUIT CHRISTMAS TREES & MANIFOLDS AS WELL AS MUD GATE VALVES 1 13/16", 2 1/16", 2 9/16", 3 1/16", 3 1/8", 4 1/16", 7 1/16", API6A 2000LB (2000PSI), 3000LB (3000PSI), 5000LB (5000PSI), 10000LB (10000PSI)

TYPE	SIZE INCH	RATING	ENDS	MANUFACTURER	DESCRIPTION	BODY	TRIM	QTY
------	-----------	--------	------	--------------	-------------	------	------	-----

FULL FACTORY MATERIAL & TEST CERTIFICATION SUPPLIED ON ALL ITEMS TO API6A/EN102014-3.1 (DIN500493.1) (FORMERLY 50049.3.1B)

WE CAN SUPPLY EQUIVALENT TO F, FL, FC STYLE MANUAL GATE VALVES AND ACTUATED GATE VALVES (HYDRAULIC & PNEUMATIC AS WELL AS EQUIVALENT MODEL 20, MODEL 120 AND TYPE M, FROM OUR USA AND EUROPEAN SUPPLIERS IN QUICK DELIVERY.

OUR INHOUSE ENGINEERING DIVISION CAN ARRANGE TO FABRICATE & TEST COMPLETE MANIFOLDS. BECAUSE WE STOCK FLANGES, TEES, ELBOWS, GATE VALVES, PLUG VALVES ETC. WE CAN MANUFACTURE IN VERY SHORT LEAD TIME.

GLOBAL SUPPLY LINE PRODUCT RANGE OILFIELD WELLHEAD GATE VALVES AND CHRISTMAS TREES (XMAS TREES)  
 XMAS TREES, MUD GATE VALVES DEMO EQUIVALENT, EXPANDING SLAB GATE VALVE WKM<sup>®</sup> 'M' EQUIVALENT AND CAMERON<sup>®</sup> FC EQUIVALENT FLOATING SLAB.

END CONNECTIONS: - RTJ (RING JOINT)

BUTTWELD SCHEDULE 40, BUTTWELD SCHEDULE 80, BUTTWELD SCHEDULE 160, NPT (LP) THREADED.

SIZE RANGE API6A (API6B) 1 13/16 INCH, 2 1/16 INCH, 2 9/16 INCH, 3 1/8 INCH, 3 1/16 INCH, 4 1/16 INCH, 7 1/16 INCH.

BODY MATERIAL: - 4130 (60K), API TYPE 2 (API-4), API TYPE 4, A487C.

SPECIFICATION: - PR1, PR2, PSL1, PSL2, TEMP. U.

API6A 2000 LB (2000 PSI), 3000 LB (3000 PSI), 5000 LB (5000 PSI), 10000 LB (10000 PSI), 15000 LB (15000 PSI)

[www.globalsupplyline.com.au](http://www.globalsupplyline.com.au)

\*Disclaimer - Cameron<sup>®</sup>, WKM<sup>®</sup> and Demco<sup>®</sup> are Registered Trademarks of Cameron International Corporation. These brands are not associated or affiliated with Global Supply Line, APV or it's manufacturers in any way, nor have these companies sponsored, approved, endorsed or otherwise reviewed any product made, sold or manufactured by Global Supply Line's manufacturers